



Evac/ASME Packaged Recovery Unit

Able to recover R22 at 325lbs/minute push/pull, 6.0lbs/minute vapor

SPECIFICATIONS

Push/Pull Rates (R22)	325-lbs/min
Vapor Rates (R22)	6.0-lbs/min
Float Connection	3-pin BH
Connections	3/4" flare
Low Pressure Switch	15" Hg
Liquid and Vapor ports:	3/4" threaded connect

Evac/ASME Tank Mount

High Speed, High Efficiency Recovery and storage of all High Pressure Refrigerants

- **Packaged recovery/storage unit for high pressure refrigerants**
- **Unit is hard piped and permanently mounted on ASME tank**
- **For use with large tonnage chillers**
- **Capable of storing up to 6448lbs of R134a at 80% capacity**
- **Dual 250-psi relief valves on diverting valve**
- **Mounted on casters for mobility**
- **80% tank full float switch and 12' cable**
- **Bottom drain connection**
- **ion with isolation ball valves**
- **ETL certified**

Certifications Certified by ETL to UL-1963 standards
Rated in accordance with ARI Standard 740-1998

Order Number	Specifications	Tank/gal	Weight	Condensator
CRH-A-240-1-250	230/60/1, 220/50/1, 3hp, 15A	250	2225	AIR
CRH-A-230-3-250	230/60/3, 220/50/3, 3hp, 20a	250	2225	AIR
CRH-A-460-3-250	460/60/3, 415/50/3, 3hp, 15A	250	2225	AIR
CRH-W-240-1-250	230/60/1, 220/50/1, 3hp, 15A	250	2225	AIR/WATER
CRH-W-230-3-250	230/60/3, 220/50/3, 3hp, 20a	250	2225	AIR/WATER
CRH-W-460-3-250	460/60/3, 415/50/3, 3hp, 15A	250	2225	AIR/WATER
CRH-A-240-1-500	230/60/1, 220/50/1, 3hp, 15A	500	2450	AIR
CRH-A-230-3-500	230/60/3, 220/50/3, 3hp, 20a	500	2050	AIR
CRH-A-460-3-500	460/60/3, 415/50/3, 3hp, 15A	500	2450	AIR
CRH-W-240-1-500	230/60/1, 220/50/1, 3hp, 15A	500	2450	AIR/WATER
CRH-W-230-3-500	230/60/3, 220/50/3, 3hp, 20a	500	2450	AIR/WATER
CRH-W-460-3-500	460/60/3, 415/50/3, 3hp, 15A	500	2450	AIR/WATER
CRH-A-240-1-850	230/60/1, 220/50/1, 3hp, 15A	850	2950	AIR
CRH-A-230-3-850	230/60/3, 220/50/3, 3hp, 20a	850	2950	AIR
CRH-A-460-3-850	460/60/3, 415/50/3, 3hp, 15A	850	2950	AIR
CRH-W-240-1-850	230/60/1, 220/50/1, 3hp, 15A	850	2950	AIR/WATER
CRH-W-230-3-850	230/60/3, 220/50/3, 3hp, 20a	850	2950	AIR/WATER
CRH-W-460-3-850	460/60/3, 415/50/3, 3hp, 15A	850	2950	AIR/WATER

INCLUDED

- One 48cu" filter core
- One 10' x 3/4" diameter hose
- Two 20' x 3/4" diameter hoses
- 100' power cord for controls
- 50' power cord for unit
- 12' tank float cable
- Two each 3/4"-5/8" and 5/8"-1/2" reducing fittings