



Blazing Recovery Rates to Service Chillers & Other Large Cooling Systems

- Recovers R22 at 325-lb/min liquid & 6-lb/min vapor!
- Rugged open drive compressor provides years of reliable service, even on refrigerants heavily contaminated with oil, air, moisture, & acids. Equipped with in-line oil separator.
- Services R12, R22, R134a, R502, R410a & other high-pressure refrigerants.

Easy Operations

- Purging lines and switching from liquid to vapor recovery modes simply involves turning three 3way hand valves and rerouting one hose.

Specifications

Push/Pull Rates	(R22) 325-lbs/min	(R134a) 307-lbs/min	(R410a) 295-lbs/min
Vapor Rates	(R22) 6.0-lbs/min	(R134a) 5.11-lbs/min	(R410a) 4.95-lbs/min
Dimensions (lwxh in inches)	32" x 29" x 45"	Shipping (48" x 40" x 51")	406 lbs (471 lbs dual voltage)
Float Connection	3-pin BH		
Connections	3/4" flare		
Low Pressure Switch	15" Hg		
Certifications standards	Certified by ETL to UL-1963		

Rated in accordance with
ARI Standard 740-1998

Included with purchase

One 48-cubic inch drier core	50-ft power cord for controls (115V for 3Ph and dual voltage models)
12-ft tank float cable	50-ft power cord for recovery unit
(2) 3/4"-5/8" & 5/8-1/2" fittings	Two 3/4" x 10ft & One 3/4" x 20ft recovery hoses w/ ball valves

Order number	Power options	Controls / Cooling option	Weight (lbs)
CRH-A-230-3-E	220-240V,50/60Hz,3Ph,3Hp,20A	Electromechanical Controls, Air Cooled	260
CRH-A-240-1-E	220-240V,50/60Hz,1Ph,3Hp,30A	Electromechanical Controls, Air Cooled	260
CRH-A-460-3-E	360-575V,50/60Hz,3Ph,3Hp,15A	Electromechanical Controls, Air Cooled	260
CRH-A-D24-1-E	240/460V 50/60Hz,1PH,5Hp,30A	Electromechanical Controls, Air Cooled	325
CRH-W-230-3-E	220-240V,50/60Hz,3Ph,3Hp,20A	Electromechanical Controls, Air/Water Cooled	265
CRH-W-240-1-E	220-240V,50/60Hz,1Ph,3Hp,30A	Electromechanical Controls, Air/Water Cooled	265
CRH-W-460-3-E	360-480V,50/60Hz,3Ph,3Hp,15A	Electromechanical Controls, Air/Water Cooled	265
CRH-W-D24-1-E	240/460V,50/60Hz,1Ph,5Hp,30A	Electromechanical Controls, Air/Water Cooled	330

RefTec International Sytems, LLC
6950 112th Circle
Largo, Fl. 33773

Toll Free Tel: 800-214-4883
Factory Tel: 727-290-9830
Sales Fax: 727-827-2882

www.reftec.com