



HYPERWATT Water Heating Chiller Pressurizer

Higher 30kW Capacity Rapidly Pressurizes a Chiller



Portable Service Cart Model

- Microprocessor displays step-by-step operating instructions.
- When desired chiller pressure level is reached, the pump shuts down. Automatically re-energizes to maintain stable pressure.
- Microprocessor monitors chiller pressure and prevents over-pressurization.
- Thermal sensors prevent heating element overload and burnout.
- Sensor halts operations should water flow cease.
- 100-lb portable model easily managed by one man and maneuvered around tight mechanical rooms.
- Permanent mount unit is hard piped to a chiller. Maintains the chiller at slightly positive pressure during seasonal shutdown.

EPA,CE,CSA certified through AHRI.

Specifications

Power: Controls & Water Pump
Dimensions – Inches: l x w x h
Weight
Pressure settings

115/60/1 110/50/1
20 x 22 x 51
100-lbs
0 to 10-psi

Included with purchase

50-ft power cord for controls
50-ft power cord for recovery unit
20-ft x ¼” refrigerant hose
Two 15-ft water hoses
Two ¾” water swivel fittings

Order Number

HPS-C-D24-3
HPS-P-D24-3
HPS-C-575-3
HPS-P-575-3

Voltage Options

220-480V,50/60Hz,3Ph,20/40A
220-480V,50/60Hz,3Ph,20/40A
575V,50/60Hz,3Ph, 20/40A
575V,50/60Hz,3Ph, 20/40A

Model

Service Cart
Permanent Mount
Service Cart
Permanent Mount

RefTec International, Inc.
10530 Portal Crossing W,
Suite 104
Bradenton, FL 34211

Tel: 800-214-4883
fax: 941-750-0222
www.reftec.com
email: sales@reftec.com